## NSN 3020-01-238-8337

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-238-8337 **Body Style:** Webbed, with lightening holes **Spline Quantity:** 14 both ends **Attachment Method:** Mounting hole Pitch Diameter: 4.4444 inches **Teeth Quantity:** 40 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.5833 inches both ends Hardness Rating: 31.0 rockwell c and 36.0 rockwell c **Mounting Hole Type And Quantity:** 4 plain axially through body, first end **Outside Diameter:** 4.667 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Face Width:** 0.250 inches **Bore Diameter:** 0.644 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 0.875 inches both ends **Precision Classification:** Quality number 8 **Mounting Hole Diameter:** 0.094 inches axially through body, first end **Special Features:** With 4 lightening holes equally spaced within 0.060 in, 1.250 in dia Material: Steel comp 4140

**Material Specification:** 

Mil-s-5626 military specification single material response

## NSN 3020-01-238-8337

Spur Gear - Page 2 of 2

Mil-s-5626 spec.



Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class 1 federal specification single treatment response
Style Designator:
Flush hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):