## NSN 3020-01-260-4452

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-260-4452

Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
1.7708 inches
Teeth Quantity:
85
Bore Style:
10a w/ keyway both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
3 threaded transversely through hub, first end
Outside Diameter:
1.812 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.059 inches second end
Face Width:
0.188 inches
Bore Diameter:
0.750 inches both ends
Keyway Width:
0.094 inches both ends
Distance From Bore Center To Keyway Bottom:
0.438 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
1.164 inches first end
Precision Classification:
Quality number 12
Special Features:
Mounting holes 120 degrees apart
Material:
Stainless steel

Material Specification:

Ms5643 assn standard single material response

## **NSN 3020-01-260-4452** Spur Gear - Page 2 of 2

spec.



Surrace Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 2 or 8 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):