# NSN 3020-01-260-4452

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-260-4452

# Body Style:

Plain, with lightening holes

## **Attachment Method:**

Mounting hole

## **Pitch Diameter:**

1.7708 inches

## **Teeth Quantity:**

85

## Bore Style:

10a w/ keyway both ends

## Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

### Mounting Hole Thread Size:

0.138 inches transversely through hub, first end

## Mounting Hole Type And Quantity:

3 threaded transversely through hub, first end

### **Outside Diameter:**

1.812 inches

# **Pressure Angle:**

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.059 inches second end

# Face Width:

0.188 inches

#### Bore Diameter:

0.750 inches both ends

#### Keyway Width:

0.094 inches both ends

## Distance From Bore Center To Keyway Bottom:

0.438 inches both ends

## Hub Style Designator:

Plain both ends

## Hub Diameter:

1.164 inches first end

#### **Precision Classification:**

Quality number 12

#### **Special Features:**

Mounting holes 120 degrees apart

Material:

Stainless steel

## **Material Specification:**

Ms5643 assn standard single material response

# NSN 3020-01-260-4452

Spur Gear - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 or 8 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

spec.