NSN 3020-01-268-7470



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-268-7470 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **End Application:** 3810-01-205-2716, crane, wheel mtd Pitch Diameter: 3.7500 inches **Teeth Quantity:** 45 **Bore Style:** 10a w/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end Hardness Rating: 450.0 brinell standard teeth and 500.0 brinell standard teeth **Mounting Hole Thread Size:** 0.257 inches axially through body, first end **Mounting Hole Type And Quantity:** 2 threaded axially through body, first end **Outside Diameter:** 3.802 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Face Width:** 1.375 inches **Bore Diameter:** 1.378 inches both ends **Keyway Width:** 0.314 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.829 inches both ends **Bolt Hole Circle Diameter:** 3.000 inches axially through body, first end Material: Steel comp 8620 or steel comp 4320 **Style Designator:** Hubless Shelf Life:

N/a

NSN 3020-01-268-7470 Spur Gear - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A27300