NSN 3020-01-273-4784

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-273-4784

Outside Diameter:
1.620 inches
Overall Length:
1.010 inches
Outside Diameter:
1.620 inches
Drilled Hole Diameter:
0.159 inches
Flange Quantity:
2
Securing Hole Quantity:
3
Face Width:
0.660 inches
Design Form:
Webbed
Hole Location:
2nd end, 0.850 in. Lg
Securing Method:
Drilled hole
Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Offset
Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Rim Type:
Solid
Flange Location:
Inside and outside
Bore Feature:
Not included
Protruding Hub Characteristic:
Stepped
Securing Location:
Bb end
Hub End Outside Diameter And Location:
1.313 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.300 inches aa end

NSN 3020-01-273-4784

Flat Pulley - Page 2 of 2



First Step Face Largest Diameter And Location:
1.313 inches aa end
First Step Length And Location:
0.050 inches aa end
Second Step Length And Location:
0.250 inches aa end
Hub End Outside Diameter And Location:
1.200 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.300 inches aa end
Special Features:
60 degrees wedge cut from outer edge to center, 0.190 r at point; 2 tap drilled holes in wede side 0.330 in. Deep, csk 82 degx0.157 in. Dia
0.138-32 unc 2bx0.220 min. Full thread
Surface Treatment:
Anodize
Style Designator:
Plain
Surface Treatment:
Anodized
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a