NSN 3020-01-280-5004

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-280-5004

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| End Application: |
| Lantirn navigation pod |
| Pitch Diameter: |
| 4.3750 inches |
| Teeth Quantity: |
| 210 |
| Bore Style: |
| W/counterbore both ends |
| Mounting Hole Thread Series Designator: |
| Unc axially through body, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 56 axially through body, first end |
| Mounting Hole Thread Size: |
| 0.086 inches axially through body, first end |
| Mounting Hole Type And Quantity: |
| 8 threaded axially through body, first end |
| Outside Diameter: |
| 4.417 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Body Recess Depth: |
| 0.215 inches second end |
| Face Width: |
| 0.550 inches |
| Bore Diameter: |
| 3.350 inches both ends |
| Counterbore Depth: |
| 0.245 inches first end |
| Counterbore Diameter: |
| 4.000 inches second end |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.245 inches first end |
| End Diameter: |

4.000 inches first end

NSN 3020-01-280-5004 Spur Gear - Page 2 of 2



| First Step Length: |
|--|
| 0.125 inches first end |
| First Step Diameter: |
| 4.160 inches first end |
| Material: |
| Steel |
| Material Specification: |
| Ams5643 assn standard single material response |
| Style Designator: |
| Hubless, recessed body |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A27300