## NSN 3020-01-283-3906

Spur Antibacklash Gear - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-01-283-3906

| Attachment Method:                                 |  |
|--|--|
| Mounting hole                                      |  |
| Pitch Diameter:                                    |  |
| 5.8750 inches                                      |  |
| Teeth Quantity:                                    |  |
| 47   |  |
| Bore Style:  |  |
| Plain both ends                                    |  |
| Mounting Hole Type And Quantity:                   |  |
| 1 plain transversely through hub, first end        |  |
| Outside Diameter:                                  |  |
| 6.182 inches                                       |  |
| Pressure Angle:                                    |  |
| 20.0000 degrees                                    |  |
| Distance Between Body Face And Protruding Hub End: |  |
| 0.590 inches first end                             |  |
| Face Width:  |  |
| 0.190 inches                                       |  |
| Bore Diameter:                                     |  |
| 0.499 inches both ends                             |  |
| Hub Style Designator:                              |  |
| Pinned first end                                   |  |
| Hub Diameter:                                      |  |
| 0.865 inches first end                             |  |
| Mounting Hole Diameter:                            |  |
| 0.086 inches transversely through hub, first end   |  |
| Material:  |  |
| Steel comp 303                                     |  |
| Style Designator:                                  |  |
| Protruding hub                                     |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:                                   |  |
|  |  |
| Demilitarization:                                  |  |
| No   |  |
| Fiig:  |  |
|  |  |