

View Online at <https://aerobasegroup.com/nsn/3020-01-284-5410>

End Application:

Uals adapter

Bore Style:

W/counterbore both ends

Design Type:

Spur all gears

Construction:

Assembled

Hardness Rating:

30.0 rockwell c and 35.0 rockwell c

Outside Diameter:

2.453 inches second gear

Nominallength:

1.590 inches

Bore Diameter:

0.375 inches both ends

Counterbore Depth:

0.430 inches both ends

Counterbore Diameter:

0.501 inches both ends

Hub Style Designator:

1 step both ends

Hub Diameter:

0.620 inches both ends

Special Features:

1st gear data: no. Of teeth 30; pitch dia. 2.3077; pressure angle 20.0000; 2nd gear data: no. Of teeth 12; pitch dia. 1.0000; pressure angle 20.0000

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Astma322 assn standard single material response or astma331 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A270a0

Mil-std (military Standard):

Mil-std-171 spec.