NSN 3020-01-286-4532

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-286-4532

Body Style:

Webbed, offset, solid

Spline Quantity:

6 both ends

Pitch Diameter:

2.0625 inches

Teeth Quantity:

99

Bore Style:

Involute spline both ends

Spline Pitch Diameter:

0.3750 inches both ends

Backlash Designation:

Grade c

Outside Diameter:

2.104 inches

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.467 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.438 inches both ends

Hub Style Designator:

Plain both ends

Hub Diameter:

1.953 inches second end

Precision Classification:

Quality number 10

Material:

Steel comp xm-12

Material Specification:

Ams5659 assn standard single material response

Surface Treatment:

Lubricant dry film teeth

Surface Treatment Specification:

Mil-I08937 military specification single treatment response spline

Style Designator:

Protruding hubs

Shelf Life:

N/a

NSN 3020-01-286-4532

Spur Gear - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-I-8937 spec.

