NSN 3020-01-286-7660

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-286-7660

| Body Style: | | | | |
|---|--|--|--|--|
| Plain, solid | | | | |
| Pitch Diameter: | | | | |
| 0.2861 inches | | | | |
| Teeth Quantity: | | | | |
| 17 | | | | |
| Hardness Rating: | | | | |
| 37.0 rockwell c and 39.0 rockwell c | | | | |
| Outside Diameter: | | | | |
| 0.297 inches | | | | |
| Teeth Type: | | | | |
| Single helix | | | | |
| Tooth Form: | | | | |
| Stub | | | | |
| Tooth Direction: | | | | |
| Left | | | | |
| Pressure Angle: | | | | |
| 20.0000 degrees | | | | |
| Helix Angle: | | | | |
| 21.8305 degrees | | | | |
| Distance Between Body Face And Protruding Hub End: | | | | |
| 0.382 inches first end | | | | |
| Face Width: | | | | |
| 0.280 inches | | | | |
| Hub Style Designator: | | | | |
| Pinned first end | | | | |
| Hub Diameter: | | | | |
| 0.210 inches first end | | | | |
| Precision Classification: | | | | |
| Quality number 12 | | | | |
| Material: | | | | |
| Steel comp 4340 | | | | |
| Material Specification: | | | | |
| Mil-s-5000 military specification single material response | | | | |
| Surface Treatment: | | | | |
| Copper | | | | |
| Surface Treatment Specification: | | | | |
| Mil-c-14550, class 2 military specification single treatment response | | | | |
| Style Designator: | | | | |
| Protruding hub | | | | |
| Shelf Life: | | | | |
| N/a | | | | |

NSN 3020-01-286-7660

Helical Gear - Page 2 of 2



| П | Init | 7 1+ | Measure: |
|---|-------|------|-----------|
| u | ,,,,, | v | wicasuic. |

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.