NSN 3020-01-286-9474



Flat Pulley - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-286-9474 **Outside Diameter:** 2.001 inches **Overall Length:** 1.460 inches **Bore Diameter:** 0.375 inches **Bore Length:** 1.120 inches **Securing Hole Quantity:** 3 **Material And Location:** Aluminum alloy, qq-a-200/8, alloy 6061, t6 body or aluminum alloy, qq-a-225/8, alloy 6061, t6 body or aluminum alloy, qq-a-250/11, alloy 6061, t6 body and steel, qq-s-763, class 410, cond a hub or steel, qq-s-763, class 416, cond a hub **Face Width:** 0.500 inches **Design Form:** Plain **Bore Type:** Straight Bearings: Included **Counterbore Feature:** Not included **Bearing Quantity:** 2 **Keying Facility:** Not included **Securing Method:** Drilled hole **Split Hub Feature:** Not included **Lightening Hole:** Not included **Integral Cooling Vane:** Not included **Crown Face:** Included

Bore Feature:
Included
Bearing Type:
Flanged

Rim Type: Single split

NSN 3020-01-286-9474 Flat Pulley - Page 2 of 2



Protruding Hub Characteristic:
Stepped
Securing Location:
Aa end
Hub End Outside Diameter And Location:
0.622 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.840 inches aa end
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Chemical film and passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a