NSN 3020-01-298-2675

Bevel Gear - Page 1 of 2

Body Style: Plain, solid



View Online at https://aerobasegroup.com/nsn/3020-01-298-2675

| Spline Quantity: |
|--|
| 15 both ends |
| End Application: |
| F-15 acft |
| Pitch Diameter: |
| 2.4000 inches |
| Teeth Quantity: |
| 24 |
| Bore Style: |
| Involute spline both ends |
| Spline Pitch Diameter: |
| 0.4688 inches both ends |
| Hardness Rating: |
| 30.0 rockwell c and 35.0 rockwell c |
| Outside Diameter: |
| 2.525 inches |
| Nominallength: |
| 0.810 inches |
| Teeth Type: |
| Straight |
| Pressure Angle: |
| 20.0000 degrees |
| Pitch Angle: |
| 37.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.250 inches second end |
| Face Width: |
| 0.560 inches |
| Bore Diameter: |
| 0.405 inches both ends |
| Hub Style Designator: |
| Plain second end |
| Hub Diameter: |
| 0.720 inches second end |
| Precision Classification: |
| Quality number 6 |
| Material: |
| Steel comp 4130 or steel comp 4140 |

Astm-a322 assn standard 1st material response or astm-a331 assn standard 2nd material response

Material Specification:

NSN 3020-01-298-2675

Bevel Gear - Page 2 of 2

Mil-std-171 spec.



| Surface Treatment: |
|--|
| Phosphate |
| Surface Treatment Specification: |
| Mil-std-171 military specification single treatment response |
| Style Designator: |
| Peripheral face, back hub protruding |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |
| Mil-std (military Standard): |