NSN 3020-01-298-2681

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-298-2681

Body Style:

Spoked

Spline Quantity:

15 first end

End Application:

F-15 aircraft a/c

Pitch Diameter:

2.6667 inches

Teeth Quantity:

32

Bore Style:

Involute spline first end

Spline Pitch Diameter:

0.4669 inches first end

Outside Diameter:

2.862 inches

Nominallength:

0.710 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.460 inches first end

Body Recess Depth:

0.420 inches second end

Face Width:

0.250 inches

Bore Diameter:

0.406 inches first end

Hub Style Designator:

1 step first end

End Length:

0.060 inches first end

Precision Classification:

Quality number 8

End Diameter:

0.610 inches first end

First Step Length:

0.200 inches first end

First Step Diameter:

0.740 inches first end

NSN 3020-01-298-2681

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6 federal specification single material response

Surface Treatment:

Lubricant dry film

Surface Treatment Specification:

Mil-std-171 military specification single treatment response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.