## NSN 3020-01-298-2686

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-298-2686

Body Style:
Webbed, solid
Attachment Method:
Clamp
End Application:
F-15 a/c acft
Pitch Diameter:
3.6667 inches
Teeth Quantity:
44
Bore Style:
Plain both ends
Hardness Rating:
30.0 rockwell c and 35.0 rockwell c
Outside Diameter:
3.898 inches
Nominallength:
0.635 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.335 inches second end
Face Width:
0.300 inches
Bore Diameter:
0.874 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
1.700 inches second end
Precision Classification:
Quality number 8
Material:
Steel comp 4130 or steel comp 4140
Material Specification:
Astm-a322 assn standard 1st material response or astm-a331 assn standard 2nd material response
Surface Treatment:
Phosphate
Surface Treatment Specification:

Mil-std-171 military specification single treatment response

## NSN 3020-01-298-2686

Spur Gear - Page 2 of 2



Style Designator:
One protruding hub, one flush hub
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.