NSN 3020-01-298-6781

Spur Gear - Page 1 of 2

Webbed, with lightening holes

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-01-298-6781

Pitch Diameter:
3.6000 inches
Teeth Quantity:
72
Bore Style:
W/counterbore both ends
Hardness Rating:
30.0 rockwell c and 35.0 rockwell c
Outside Diameter:
3.686 inches
Nominallength:
0.507 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.197 inches second end
Body Recess Depth:
0.070 inches first end
Face Width:
0.310 inches
Bore Diameter:
0.687 inches both ends
Counterbore Depth:
0.050 inches second end
Counterbore Diameter:
0.737 inches second end
Hub Style Designator:
Plain second end
Hub Diameter:
0.930 inches second end
Precision Classification:
Quality number 8
Special Features:
5 lightening holes 0.750 in.
Material:
Steel comp 4130 or steel comp 4140
Material Specification:

Astm-a322 assn standard 1st material response or astm-a331 assn standard 2nd material response

NSN 3020-01-298-6781

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-std-171 spec.



Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-std-171 military specification single treatment response
Style Designator:
Protruding hub, recessed body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A27300