NSN 3020-01-315-4442

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-315-4442 **Attachment Method:** Mounting hole **Teeth Quantity:** 22 **Bore Style:** W/stepped counterbore first end Pitch Radius: 4.5000 inches **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.250 inches axially through body, first end **Mounting Hole Type And Quantity:** 6 threaded axially through body, first end **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Face Width: 2.380 inches **Bore Diameter:** 2.750 inches both ends **Counterbore Depth:** 1.750 inches second counterbore, first end **Counterbore Diameter:** 4.250 inches first counterbore, first end **Outside Radius:** 4.633 inches Arc Length: 11.519 inches **Bolt Hole Circle Diameter:** 3.562 inches axially through body, first end **Special Features:** Clevis opposite gear teeth, 0.879 in.Between forks, 0.440 in.Thk forks, 2 holes in line through clevis, 0.875 in.Dia, clevis 1.990 in.Dp Material: Steel **Material Specification:**

Style Designator: Hubless

Mil-s-16216 military specification single material response

Hubless

Shelf Life:

N/a

NSN 3020-01-315-4442

Spur Gear Sector - Page 2 of 2



Unit Of Meası

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-16216 spec.