NSN 3020-01-322-1002

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-322-1002 **Body Style:** Webbed, with lightening holes Pitch Diameter: 6.9167 inches **Teeth Quantity:** 83 **Bore Style:** 10a w/ keyway both ends **Hardness Rating:** 55.0 rockwell c and 58.0 rockwell c **Outside Diameter:** 7.062 inches **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.625 inches first end **Face Width:** 0.500 inches **Bore Diameter:** 1.625 inches both ends **Keyway Width:** 0.375 inches both ends **Distance From Bore Center To Keyway Bottom:** 1.312 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 2.620 inches first end Material: Steel comp 8620 **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232, type m, class 2 military specification all treatment responses **Style Designator:** One protruding hub, one flush hub Shelf Life: **Unit Of Measure:**

N/a **Demilitarization:** No

NSN 3020-01-322-1002

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.