NSN 3020-01-322-1003

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-322-1003 **Body Style:** Webbed, with lightening holes Pitch Diameter: 10.0000 inches **Teeth Quantity:** 100 **Bore Style:** 10b w/ 2 keyways both ends **Hardness Rating:** 55.0 rockwell c and 58.0 rockwell c **Outside Diameter:** 10.175 inches **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.375 inches first end **Face Width:** 0.875 inches **Bore Diameter:** 2.312 inches both ends **Keyway Width:** 0.375 inches both ends **Distance From Bore Center To Keyway Bottom:** 2.218 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 3.360 inches both ends Material: Steel comp 8620 **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232, type m, class 2 military specification all treatment responses **Style Designator:** One protruding hub, one flush hub Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 3020-01-322-1003

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.