NSN 3020-01-344-1890

Spur Gear - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/3020-01-344-1890

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| 0.6250 inches |
| Teeth Quantity: |
| 40 |
| Bore Style: |
| W/counterbore counterbore, first end |
| Features Provided: |
| Special marking |
| Outside Diameter: |
| 0.654 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.260 inches first end |
| Body Recess Depth: |
| 0.216 inches first end |
| Face Width: |
| 0.055 inches |
| Bore Diameter: |
| 0.250 inches both ends |
| Counterbore Depth: |
| 0.026 inches counterbore, first end |
| Counterbore Diameter: |
| 0.312 inches counterbore, first end |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.735 inches first end |
| Special Features: |
| Hub face has numerals and index lines painted on; numerals 0 through 9 to be spaced each 36 degrees, major index lines to be spaced |
| each 36 degrees at numerals, and minor index lines to be spaced each 18 degrees between major lines |
| Material: |
| Plastic acetal |
| Style Designator: |
| Protruding hub, recessed body |
| Furnished Items And Quantity: |
| 1 lubricant impregnated bearing |
| Shelf Life: |

NSN 3020-01-344-1890 Spur Gear - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

Demilitarization:

No

Fiig:

A27300