NSN 3020-01-345-5799

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-345-5799

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.7344 inches |
| Teeth Quantity: |
| 111 |
| Bore Style: |
| Partial both endspartial second end |
| Mounting Hole Type And Quantity: |
| 1 countersunk axially through body, first end and 1 plain axially through body, first end |
| Outside Diameter: |
| 1.766 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.219 inches first end |
| Face Width: |
| 0.093 inches |
| Bore Diameter: |
| 0.187 inches second end |
| Bore Depth: |
| 0.219 inches second end |
| Hub Style Designator: |
| Pinned first end |
| Hub Diameter: |
| 0.375 inches first end |
| Mounting Hole Diameter: |
| 0.250 inches axially through body, first end and 0.125 inches axially through body, first end |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6 federal specification single material response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 3020-01-345-5799

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300