NSN 3020-01-346-1865



Spur Gear - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/3020-01-346-1865
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
7.0000 inches
Teeth Quantity:
448
Bore Style:
Plain both ends
Hardness Rating:
28.0 rockwell c and 37.0 rockwell c
Mounting Hole Type And Quantity:
2 plain axially through body, first end10 plain axially through body, second end
Outside Diameter:
7.030 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.133 inches second end
Body Recess Depth:
0.087 inches first end
Face Width:
0.187 inches
Bore Diameter:
5.562 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
6.182 inches second end
Mounting Hole Diameter:
0.156 inches axially through body, first end0.140 inches axially through body, second end
Bolt Hole Circle Diameter:
5.800 inches axially through body, second end
Special Features:
Second end also recessed 0, 133 in., 6.000 in. Dia.
Material:
Stainless steel
Material Specification:
Ams 5643 condtn 1150 assn standard single material response
Surface Treatment:
Oxide

NSN 3020-01-346-1865

Spur Gear - Page 2 of 2



Surface Treatment Specification:

Mil-c-13924 cl (fs10020) military specification single treatment response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-13924 spec.