NSN 3020-01-348-1588



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-348-1588 **Pitch Diameter:** 0.9375 inches **Teeth Quantity:** 90 **Bore Style:** Plain both ends **Outside Diameter:** 0.958 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.221 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.120 inches first end **Hub Style Designator:** 1 step first end **End Length:** 0.180 inches first end **End Diameter:** 0.187 inches first end First Step Length: 0.041 inches first end First Step Diameter: 0.495 inches first end **Special Features:** Hub has split 0.180 in. From end Steel comp 303 first gearsteel comp 303 hubsteel comp 303 second gear **Material Specification:** Astm a582 assn standard single material response first gearastm a582 assn standard single material response hubastm a582 assn standard single material response second gear **Surface Treatment:**

Passivate first gearpassivate hubpassivate second gear

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response first gearqq-p-35 federal specification single treatment response hubqq-p-35 federal specification single treatment response second gear

Style Designator:

Protruding hub

Shelf Life:

N/a

NSN 3020-01-348-1588

Spur Antibacklash Gear - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A27300