NSN 3020-01-348-1588

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-348-1588

Pitch Diameter:

0.9375 inches

Teeth Quantity:

90

Bore Style:

Plain both ends

Outside Diameter:

0.958 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.221 inches first end

Face Width:

0.104 inches

Bore Diameter:

0.120 inches first end

Hub Style Designator:

1 step first end

End Length:

0.180 inches first end

End Diameter:

0.187 inches first end

First Step Length:

0.041 inches first end

First Step Diameter:

0.495 inches first end

Special Features:

Hub has split 0.180 in. From end

Material:

Steel comp 303 first gearsteel comp 303 hubsteel comp 303 second gear

Material Specification:

Astm a582 assn standard single material response first gearastm a582 assn standard single material response hubastm a582 assn standard single material response second gear

Surface Treatment:

Passivate first gearpassivate hubpassivate second gear

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response first gearqq-p-35 federal specification single treatment response hubqq-p-35 federal

specification single treatment response second gear

Style Designator:

Protruding hub

Shelf Life:

N/a

NSN 3020-01-348-1588

Spur Antibacklash Gear - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

