## NSN 3020-01-352-9118

Spur Gear - Page 1 of 2

**Body Style:** 

Mounting hole

Pitch Diameter:

1.1339 inches

Webbed, offset, solid **Attachment Method:** 



View Online at https://aerobasegroup.com/nsn/3020-01-352-9118

Teeth Quantity:
96
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
2 plain axially through body, first end
Outside Diameter:
1.157 inches
Pressure Angle:
15.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.168 inches first end0.170 inches second end
Face Width:
0.062 inches
Bore Diameter:
0.240 inches both ends
Hub Style Designator:
Plain first end1 groove second end
Hub Diameter:
1.062 inches first end0.500 inches second end
Precision Classification:
Accuracy grade 11
First Groove Width:
0.039 inches second end
First Groove Diameter:
0.468 inches second end
Mounting Hole Diameter:
0.128 inches axially through body, first end
Bolt Hole Circle Diameter:
0.438 inches axially through body, first end
Special Features:
Second end recessd body 0.055 in. Deep, 0.820 in. Od
Material:
Steel comp 303
Material Specification:
Astm a582 cond a assn standard single material response

## NSN 3020-01-352-9118

Spur Gear - Page 2 of 2

A27300



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 1 federal specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: