NSN 3020-01-353-0777

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-353-0777

New Online at https://defobasegroup.com/nsii/3020-01-303-0/14
Outside Diameter:
8.924 inches
Overall Length:
2.000 inches
Keyway Width:
0.625 inches
Bore Diameter:
2.438 inches
Bore Length:
2.000 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.312 inches
Face Width:
0.924 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
40.0 rockwell c body and 55.0 rockwell c body
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Belt/chain/film Size For Which Designed:
Positive drive belt
Teeth Row Quantity:
1
Teeth Quantity Per Row:
17
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:

Between 40.0 rockwell c and 55.0 rockwell c

NSN 3020-01-353-0777 Sprocket Wheel - Page 2 of 2

	Bore Bearing:
	lot included
	lub External Keyway:
	lot included
	ooth Pitch:
	.500 inches
ł	lub End Outside Diameter And Location:
Ę	250 inches aa end
[Distance From Outside Flange/rim To Hub End And Location:
1	.076 inches aa end
ľ	faterial:
ŝ	Steel, carbon
ľ	faterial:
Ś	Steel
(Quantity:
1	
Ş	Surface Treatment:
١	lickel
Ş	Style Designator:
F	Plain
Ş	Surface Treatment:
١	lickel plated
Ş	Shelf Life:
1	I/a
ι	Init Of Measure:
-	-
[Demilitarization:
١	lo
F	iig:
٦	-353-c

