NSN 3020-01-357-7173

Sprocket Wheel - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/3020-01-357-7173 **Counterbore Diameter:** 3.626 inches **Counterbore Depth:** 0.810 inches **Outside Diameter:** 6.559 inches **Overall Length:** 3.380 inches **Keyway Width:** 0.502 inches **Bore Diameter:** 2.502 inches **Bore Length:** 1.810 inches Distance From Center Of Bore To Bottom Of Keyway: 1.478 inches **Drilled Hole Diameter:** 0.250 inches and 0.344 inches Pitch Diameter: 6.667 inches **Securing Hole Quantity:** 8 **Furnished Items And Quantity:** Two bushings **Face Width:** 2.440 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Groove Quantity: Counterbore Feature:**

Counterbore Location: Bb end **Hole Location:**

Included

On sprocket face

Keying Facility:

Included

NSN 3020-01-357-7173

Sprocket Wheel - Page 2 of 3



Keying Facility Type:
Keyway
Securing Method:
Drilled hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Both ends
Belt/chain/film Size For Which Designed:
Positive drive belt
Teeth Row Quantity:
1
Teeth Quantity Per Row:
38
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.551 inches
Hub End Outside Diameter And Location:
4.250 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.940 inches aa end
Special Features:
Second counterbore located second end, 4.810 in. Dia, 0.760 in. Depth
Material:
Copper alloy
Material:
Copper alloy
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 3020-01-357-7173 Sprocket Wheel - Page 3 of 3



Fiig:

Т353-с