NSN 3020-01-383-5007

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-383-5007 **Body Style:** Webbed, with lightening holes **Spline Quantity:** 30 both ends Pitch Diameter: 3.7500 inches **Teeth Quantity:** 30 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.9375 inches both ends **Hardness Rating:** 34.0 rockwell c and 38.0 rockwell c **Outside Diameter:** 4.000 inches **Pressure Angle:** 25.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.213 inches first end **Face Width:** 1.000 inches **Bore Diameter:** 0.984 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 1.120 inches first end Material: Steel comp e4340 or steel comp 4140 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response **Surface Treatment:** Phosphate spline **Style Designator:** One protruding hub, one flush hub Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 3020-01-383-5007

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.