## NSN 3020-01-395-3984

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-395-3984 Pitch Diameter: 2.2500 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Outside Diameter:** 2.312 inches **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.239 inches second end Face Width: 0.188 inches **Bore Diameter:** 0.249 inches both ends **Hub Style Designator:** Split second end **Hub Diameter:** 0.312 inches second end **Clamping Surface Length:** 0.239 inches second end **Precision Classification:** Quality number 12 **Special Features:** One preload indication hole 0.0625 in. Diameter located axially through gear body both gears Material: Steel comp 303 spring **Material Specification:** Qq-w-423, cond b federal specification single material response spring **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Qq-p-35, type ii federal specification single treatment response hub **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 3020-01-395-3984

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.