NSN 3020-01-399-5665

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-399-5665

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
8.7500 inches
Teeth Quantity:
70
Bore Style:
10a w/ keyway both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thread Size:
0.190 inches axially through body, first end
Mounting Hole Type And Quantity:
8 threaded axially through body, first end
Outside Diameter:
8.998 inches
Tooth Form:
Stub
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.181 inches second end
Face Width:
0.627 inches
Bore Diameter:
1.125 inches both ends
Keyway Width:
0.251 inches both ends
Distance From Bore Center To Keyway Bottom:
0.678 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
2.001 inches second end
Bolt Hole Circle Diameter:
8.000 inches axially through body, first end
Special Features:
Used on high pressure watertight bulkhead door, seawolf class submarine
Material:
Bronze

NSN 3020-01-399-5665

Spur Gear - Page 2 of 2



М	ater	ial	Sp	ecifi	icati	on:

Qq-b-728 cl a federal specification single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A27300