NSN 3020-01-406-8887

Spur Gear - Page 1 of 2

Passivate



View Online at https://aerobasegroup.com/nsn/3020-01-406-8887

Body Style:
Plain, solid
Spline Quantity:
15 first end
Pitch Diameter:
1.7500 inches
Teeth Quantity:
14
Bore Style:
Plain first end
Spline Pitch Diameter:
0.4688 inches first end
Hardness Rating:
30.0 rockwell c and 35.0 rockwell c
Outside Diameter:
1.995 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
1.350 inches first end
Face Width:
0.290 inches
Bore Diameter:
0.560 inches first end
Hub Style Designator:
Plain first end
Hub Diameter:
0.880 inches first end
End Length:
0.910 inches second end
End Diameter:
0.874 inches second end
First Step Length:
0.090 inches second end
First Step Diameter:
1.230 inches second end
Material:
Steel comp xm-12
Material Specification:
Ams5659 assn standard single material response or ams5862 assn standard single material response
Surface Treatment:

NSN 3020-01-406-8887

Spur Gear - Page 2 of 2



Surface	Treatment	Specification:
Suriace	Healineil	Specification.

Astm a380 assn standard single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300