# NSN 3020-01-414-7851

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-414-7851

## **Body Style:**

Webbed, offset, solid

#### **Attachment Method:**

Mounting hole

## **End Application:**

Shotpeen mask, aircraft shop maintenance

#### Pitch Diameter:

1.2500 inches

### **Teeth Quantity:**

120

# Bore Style:

Plain both ends

### Mounting Hole Type And Quantity:

5 plain axially through body, second end

#### Outside Diameter:

1.270 inches

#### Tooth Form:

Stub

## Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.103 inches second end

#### **Body Recess Depth:**

0.064 inches first end

# Face Width:

0.085 inches

#### Bore Diameter:

0.625 inches both ends

#### Hub Style Designator:

Plain second end

#### Hub Diameter:

1.125 inches second end

### Mounting Hole Diameter:

0.129 inches axially through body, second end

### **Bolt Hole Circle Diameter:**

0.812 inches axially through body, second end

## **Special Features:**

Recess second end 0.188 in. Lg., 1.030 in. Dia

## Material:

Stainless steel

#### **Material Specification:**

Ams5659 assn standard single material response

# NSN 3020-01-414-7851

Spur Gear - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5002 spec.