NSN 3020-01-414-7959

Internal Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-414-7959

| Body Style: |
|--|
| Webbed, offset, solid |
| End Application: |
| Weapons system seawolf class ssn |
| Pitch Diameter: |
| 9.2500 inches |
| Teeth Quantity: |
| 74 |
| Bore Style: |
| W/counterbore second end |
| Hardness Rating: |
| 28.0 rockwell c body and 48.0 rockwell c body |
| Outside Diameter: |
| 10.630 inches |
| Nominallength: |
| 5.336 inches |
| Teeth Type: |
| Spur |
| Tooth Form: |
| Stub |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 2.894 inches second end |
| Face Width: |
| 1.630 inches |
| Bore Diameter: |
| 4.500 inches second end |
| Counterbore Depth: |
| 0.943 inches counter bore, second end |
| Counterbore Diameter: |
| 4.801 inches counter bore, second end |
| Hub Style Designator: |
| 2 grooves second end |
| Hub Diameter: |
| 5.750 inches second end |
| Precision Classification: |
| Accuracy grade 10 |
| First Groove Width: |
| 0.120 inches |
| First Groove Diameter: |

5.720 inches second end

NSN 3020-01-414-7959 Internal Gear - Page 2 of 2



| Distance From End To First Groove: |
|---|
| 0.390 inches |
| Second Groove Width: |
| 0.220 inches second end |
| Second Groove Diameter: |
| 5.720 inches second end |
| Distance From End To Second Groove: |
| 2.122 inches |
| Special Features: |
| Hub end external threaded 5.750-12 un-2a, and 60 splines between first and second groove, gear used on valve operator |
| Material: |
| Steel comp 4140 and steel comp 4142 |
| Material Specification: |
| Astm a322 assn standard single material response |
| Style Designator: |
| Solid back ring, protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |
| |
| |
| |