## NSN 3020-01-422-4105

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-422-4105

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **End Application:** Aircraft, airlifter c-17a **Pitch Diameter:** 2.0625 inches **Teeth Quantity:** 66 Mounting Hole Thread Series Designator: Unjc axially through body, first end **Mounting Hole Thread Size:** 0.112 inches axially through body, first end Mounting Hole Type And Quantity: 4 threaded axially through body, first end **Outside Diameter:** 2.125 inches **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.473 inches first end Face Width: 0.230 inches Hub Style Designator: Plain second end **Hub Diameter:** 0.188 inches both ends End Length: 0.305 inches first end End Diameter: 0.188 inches first end First Step Length: 0.168 inches first end First Step Diameter: 0.750 inches first end **Bolt Hole Circle Diameter:** 1.500 inches axially through body, first end Material: Steel comp xm-12

Material Specification:

Ams5659 assn standard single material response

## NSN 3020-01-422-4105

Spur Gear - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300