NSN 3020-01-422-4106

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-422-4106

| View Online at https://aerobasegroup.com/nsn/3020-01-422-41 |
|---|
| Body Style: |
| Webbed, offset, solid |
| Spline Quantity: |
| 23 both ends |
| Attachment Method: |
| Mounting hole |
| End Application: |
| Aircraft, airlifter c-17a |
| Pitch Diameter: |
| 4.0000 inches |
| Teeth Quantity: |
| 128 |
| Bore Style: |
| Involute spline both ends |
| Spline Pitch Diameter: |
| 0.7187 inches both ends |
| Mounting Hole Thread Series Designator: |
| Unjf axially through body, first end |
| Mounting Hole Thread Size: |
| 0.112 inches axially through body, first end |
| Mounting Hole Type And Quantity: |
| 4 threaded axially through body, first end |
| Outside Diameter: |
| 4.062 inches |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.031 inches first end |
| Distance Between Body Face And Recessed Hub End: |
| 0.130 inches second end |
| Face Width: |
| 0.265 inches |
| Bore Diameter: |
| 0.787 inches both ends |
| Bolt Hole Circle Diameter: |
| 2.906 inches axially through body, first end |
| Material: |
| Steel comp xm-12 |
| Material Specification: |
| Ams5659 assn standard single material response |
| Surface Treatment: |
| |

Passivate

NSN 3020-01-422-4106

Spur Gear - Page 2 of 2



Qq-p-35 federal specification single treatment response

Style Designator:

One protruding hub, one recessed hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300