NSN 3020-01-422-4106

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-422-4106

View Online at https://aerobasegroup.com/nsn/3020-01-422-41
Body Style:
Webbed, offset, solid
Spline Quantity:
23 both ends
Attachment Method:
Mounting hole
End Application:
Aircraft, airlifter c-17a
Pitch Diameter:
4.0000 inches
Teeth Quantity:
128
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
0.7187 inches both ends
Mounting Hole Thread Series Designator:
Unjf axially through body, first end
Mounting Hole Thread Size:
0.112 inches axially through body, first end
Mounting Hole Type And Quantity:
4 threaded axially through body, first end
Outside Diameter:
4.062 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.031 inches first end
Distance Between Body Face And Recessed Hub End:
0.130 inches second end
Face Width:
0.265 inches
Bore Diameter:
0.787 inches both ends
Bolt Hole Circle Diameter:
2.906 inches axially through body, first end
Material:
Steel comp xm-12
Material Specification:
Ams5659 assn standard single material response
Surface Treatment:

Passivate

NSN 3020-01-422-4106

Spur Gear - Page 2 of 2



Qq-p-35 federal specification single treatment response

Style Designator:

One protruding hub, one recessed hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300