## NSN 3020-01-425-8212



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-425-8212 **Attachment Method:** Slot **End Application:** 2320-01-123-1610 Pitch Diameter: 1.7500 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Outside Diameter:** 1.790 inches **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.221 inches second end **Face Width:** 0.104 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Split second end **Hub Diameter:** 0.310 inches second end **Clamping Surface Length:** 0.221 inches second end **Precision Classification:** Accuracy grade 12 Material: Steel comp 302 spring **Material Specification:** Astm-a582 assn standard single material response second gear **Surface Treatment:** Passivate second gear **Surface Treatment Specification:** Mil-std-171 military standard single treatment response second gear **Style Designator:** Protruding hub

Shelf Life: N/a Unit Of Measure:

## NSN 3020-01-425-8212

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.