NSN 3020-01-425-9562 Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-425-9562
Attachment Method:
Slot
End Application:
2320-01-123-1610
Pitch Diameter:
1.7500 inches
Teeth Quantity:
84
Bore Style:
Plain both ends
Outside Diameter:
1.790 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.221 inches second end
Face Width:
0.104 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Split second end
Hub Diameter:
0.248 inches second end
Clamping Surface Length:
0.221 inches second end
Precision Classification:
Accuracy grade 12
Material:
Steel comp 302 spring
Material Specification:
Astm-a582 assn standard single material response second gear
Surface Treatment:
Passivate second gear
Surface Treatment Specification:
Mil-std-171 military standard single treatment response second gear
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

NSN 3020-01-425-9562

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.