NSN 3020-01-432-2553

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-432-2553 **Body Style:** Plain, solid **Spline Quantity:** 32 both ends **End Application:** Truck, vehicle, system, 1 1/4-ton (hmmwv) Pitch Diameter: 2.6000 inches **Teeth Quantity:** 13 **Bore Style:** W/counterbore counterbore, first end **Spline Pitch Diameter:** 1.3333 inches both ends **Outside Diameter:** 3.095 inches **Pressure Angle:** 25.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.930 inches both ends Face Width: 1.880 inches **Bore Diameter:** 1.4010 inches both ends **Counterbore Depth:** 0.930 inches counterbore, first end **Counterbore Diameter:** 1.487 inches both ends **Hub Style Designator:** 1 step both ends **End Length:** 0.870 inches both ends **Precision Classification:** Quality number 6 **End Diameter:** 2.000 inches both ends

2.000 inches both ends

First Step Length:
0.060 inches both ends

First Step Diameter:
2.500 inches both ends

Material:

Steel comp 8620

NSN 3020-01-432-2553

Spur Gear - Page 2 of 2



М	ater	ial	Sp	ecifi	icati	on:

Astm a322 assn standard single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300