# NSN 3020-01-442-7278

Flat Pulley - Page 1 of 2





#### **Outside Diameter:**

12.860 inches

#### **Overall Length:**

2.545 inches

#### Bore Diameter:

Between 0.748 inches and 0.750 inches

#### Bore Length:

1.045 inches

#### **End Application:**

2320-01-314-3739

### Material And Location:

Iron, cast

#### Face Width:

1.160 inches

#### **Design Form:**

Webbed

#### \_ \_

Bore Type:

# Straight

Bearings:

Not included

### Counterbore Feature:

Not included

#### Keying Facility:

Not included

#### Split Hub Feature:

Not included

#### Web/spoke Relationship To Face Centerline:

Not offset

#### Lightening Hole:

Not included

#### Integral Cooling Vane:

Not included

#### **Crown Face:**

Not included

## Rim Type:

Solid

#### Bore Feature:

Included

#### **Protruding Hub Characteristic:**

Stepped

# Hub End Outside Diameter And Location:

4.470 inches aa end and 4.560 inches aa end

# NSN 3020-01-442-7278

Flat Pulley - Page 2 of 2



Distance From Outside Flange/rim To Hub End And Location: 0.640 inches aa end First Step Face Largest Diameter And Location: 4.560 inches aa end Second Step Face Largest Diameter And Location: 1.998 inches aa end Style Designator: Webbed or spoked Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T353-a