NSN 3020-01-450-1722

Sprocket Wheel - Page 1 of 2

Outside Diameter:



View Online at https://aerobasegroup.com/nsn/3020-01-450-1722

| 9.480 inches |
|--------------------------------|
| Overall Length: |
| 2.000 inches |
| Keyway Width: |
| 0.380 inches |
| Thread Size: |
| 3/8-16 |
| Bore Diameter: |
| 1.750 inches |
| Bore Length: |
| 2.000 inches |
| End Application: |
| Tractor, flightline towing |
| Securing Hole Quantity: |
| 1 |
| Face Width: |
| 0.580 inches |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Hole Location: |
| On hub between sprocket face |
| Keying Facility: |
| Included |
| Keying Facility Type: |
| Keyway |
| Securing Method: |
| Threaded hole |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 28 |
| Hardness Rating Test Method: |
| Not rated |

NSN 3020-01-450-1722 Sprocket Wheel - Page 2 of 2

T353-c



| Bore Bearing: |
|---|
| Not included |
| Distance From Outside Flange/rim To Hub End And Location: |
| 1.420 inches aa end |
| Material: |
| Steel |
| Material: |
| Steel |
| Quantity: |
| 1 |
| Style Designator: |
| Plain |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |