## NSN 3020-01-468-8765

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-468-8765

Body Style:
Plain, with lightening holes
End Application:
Tarawa class lha
Pitch Diameter:
2.5000 inches
Teeth Quantity:
50
Bore Style:
10a w/ keyway both ends
Outside Diameter:
2.600 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.269 inches second end
Face Width:
0.500 inches
Bore Diameter:
0.688 inches both ends
Keyway Width:
0.191 inches both ends
Distance From Bore Center To Keyway Bottom:
0.414 inches both ends
Hub Style Designator:
1 step second end
End Length:
0.969 inches second end
End Diameter:
0.773 inches second end
First Step Length:
0.700 inches second end
First Step Diameter:
2.060 inches second end
Special Features:
Gear, idler low profile monorail switch; manudactured from p/n yss2020 using altered drawing 97a0267
Material:
Steel comp 1215
Material Specification:

Aisi 1215 hrs assn standard single material response

## NSN 3020-01-468-8765

Spur Gear - Page 2 of 2



Surface Treatm	

Oil

Style Designator:

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300