

View Online at <https://aerobasegroup.com/nsn/3020-01-493-9445>

Groove Depth:

0.3386 inches

Groove Width:

1.5000 inches

Outside Diameter:

5.6772 inches

Overall Length:

1.6250 inches

Bore Diameter:

1.6563 inches

Bore Length:

0.3750 inches

End Application:

Aircraft elevator door

Groove Radius:

1.0000 inches

Material And Location:

Steel

Face Width:

1.5000 inches

Design Form:

Plain

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Keying Facility:

Not included

Securing Method:

Bolted through bore

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

U

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Both ends

Hub End Outside Diameter And Location:

2.5000 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.0625 inches both ends

Special Features:

Onha door rope support assembly; counterbore dimensions are 1.8506 in. Min and 1.810 in. Maximum for the diameter and 0.6250 for the depth; counterbores on both sides of pulley are equal in size; equipment designed for grade "a" shock resistance

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a