

View Online at <https://aerobasegroup.com/nsn/3020-01-493-9445>

**Groove Depth:**

0.3386 inches

**Groove Width:**

1.5000 inches

**Outside Diameter:**

5.6772 inches

**Overall Length:**

1.6250 inches

**Bore Diameter:**

1.6563 inches

**Bore Length:**

0.3750 inches

**End Application:**

Aircraft elevator door

**Groove Radius:**

1.0000 inches

**Material And Location:**

Steel

**Face Width:**

1.5000 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

1

**Counterbore Feature:**

Not included

**Keying Facility:**

Not included

**Securing Method:**

Bolted through bore

**Split Hub Feature:**

Not included

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

U

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Both ends

**Hub End Outside Diameter And Location:**

2.5000 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.0625 inches both ends

**Special Features:**

Onha door rope support assembly; counterbore dimensions are 1.8506 in. Min and 1.810 in. Maximum for the diameter and 0.6250 for the depth; counterbores on both sides of pulley are equal in size; equipment designed for grade "a" shock resistance

**Style Designator:**

Plain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-a