NSN 3020-01-528-7237



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-528-7237 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **End Application:** F-15 aircraft Pitch Diameter: 0.2600 inches **Teeth Quantity:** 52 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 72 transversely through hub, first end **Mounting Hole Thread Size:** 0.073 inches transversely through hub, first end **Outside Diameter:** 0.270 inches **Err Default:** Err default **Tooth Form:** Stub **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.115 inches first end **Face Width:** 0.050 inches **Bore Diameter:** 0.047 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.187 inches first end **Precision Classification:** Quality number 10 or quality number 11 **Product Name:**

Gear, spur

Special Features:

T.O. 5l6-3-65-4 fig 2-3 ind 31

NSN 3020-01-528-7237

Spur Gear - Page 2 of 2



Material:
Copper alloy 342
Material Specification:
Qq-b-613.Qq-b-613alloy 342 1/2h federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A27300

Yes - demil/mli