## NSN 3020-01-619-7024

Groove Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-619-7024 **Thread Direction:** Right-hand **Pilot Diameter:** 3.250 inches **Outside Diameter:** 4.006 inches **Bolt Circle Diameter:** 2.688 inches **Thread Size:** 0.250 **Drilled Hole Diameter:** 0.3125 inches **Pitch Diameter:** 4.010 inches **Securing Hole Quantity: Material And Location:** Iron, cast, qq-i-652, class 30 body or iron, cast, qq-i-652, class 35 body **Face Width:** Between 3.750 inches and 3.780 inches **Design Form:** Spoked **Bore Type: Tapered Groove Quantity:** 40 **Hole Location:** Aa end **Securing Method:** Threaded hole and drilled hole Web/spoke Relationship To Face Centerline: Offset **Groove Shape: Securing Location:** Aa end **Thread Size:** 

0.250 inches

**Product Name:** 

Pulley, straight bores, sychronous teeth and v-belt groove sidewalls 125 micro inch

## **Special Features:**

Max rpm: 6320; has 40 grooves, 8 mm, eq spaced; drilled holes at aa end; 5/16 dia. Thru, 3 holes at 120 degrees on 2.688 dia. Bc; drill no. 7 (.201) dia. Through c-drill 5/16 x .81dp, (from other side) tap 1/4-20 unc-2b through e holes at 120 degrees on 2.688 bhc

## NSN 3020-01-619-7024

Groove Pulley - Page 2 of 2



Surface	Treatm	ent:
---------	--------	------

Paint

**Surface Treatment:** 

Painted

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T353-a