

View Online at <https://aerobasegroup.com/nsn/3040-00-006-6095>

**General Description:**

Steel, 17.5625 o/a lg, gear data; 12 thds, 2.116 in.Min, 2.118 in.Max dia, 1.781 in.Pitch dia, 20 degrees pressure angle, 49 deg, 48 minutes pitch lead angle, 6.6206 in.Gear thd lead; stepped shaft, 1st step, 1st end, 1.625 in.Lg, 1.9995 in.Min, 2.0000 in.Max dia, 2nd step, 1 in.Lg, 1.9695 in.Min, 1.9700 in.Max dia, 3rd step, 2.8125 in.Lg, 1.6245 in.Min, 1.6250 in.Max dia, 4th step, 1.0625 in.Lg, 1.4356 in.Min, 1.4361 in.Max dia, woodruff key, tapered step, 5th step, 0.500 in.Lg, thd, 1-1/8-16 un thd size; 2nd end, 1st step 1.500 in.Lg, 1.9995 in.Min, 2.000 in.Max dia, 2nd step 1.4063 in.Min, 1.4375 in.Max in.Lg, 1.0005 in.Min, 1.0010 in.Max dia, 3rd step 0.5312 in.Lg, thd, .969-32 thd size, woodruff key, 4th step 0.250 in.Lg, 5th step 1 in.Lg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No