NSN 3040-00-009-1565

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-009-1565 First End Style: Unthreaded cross drilled **End Similarity:** Not identical Second End Style: Circular grooved and externally threaded **Second End Groove Width:** 0.0460 inches **Second End Groove Diameter:** Between 0.3000 inches and 0.3150 inches **Overall Length:** 9.000 inches First End Diameter: Between 0.4980 inches and 0.4990 inches First End Hole Diameter: 0.1940 inches First End Distance From Hole Center To End: 0.250 inches **Second End Distance From End To Groove:** 0.875 inches **Second End Diameter:** 0.3750 inches Second End External Thread Length: 0.875 inches Step Quantity: 5 **Largest Step Diameter:** Between 0.498 inches and 0.499 inches **Surface Finish:** 63.0 microinches Material: Steel comp 303 or steel comp 304 **Material Specification:** Mil-s-7720 military specification all material responses **Fsc Application Data:** Test bench set, specially designed, acft Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 3040-00-009-1565

Shouldered Shaft - Page 2 of 2



Fiig:

A23200

Mil-std (military Standard):

Mil-s-7720 spec.