NSN 3040-00-024-5960

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-024-5960

First End Style:
Cross drilled and externally threaded
End Similarity:
Not identical
Second End Style:
Two circular grooves and splined (straight_)
Second End Groove Diameter:
Between 0.2810 inches and 0.2850 inches
Overall Length:
8.4060 inches
End Application:
Part of pressurizing and cutoff body gp for main fuel control, aj-a2, j57 aircraft
First End Diameter:
Between 0.3059 inches and 0.3125 inches
First End Hole Diameter:
Between 0.0740 inches and 0.0780 inches
First End Distance From Hole Center To End:
0.208 inches
First End External Thread Length:
0.594 inches
Second End Diameter:
Between 0.3744 inches and 0.3747 inches
Second End Spline Length:
1.062 inches
Second End Spline Minor Diameter:
0.3500 inches
Second End Spline Major Diameter:
0.3740 inches
Second End Distance Between First And Second Groove Centers:
0.562 inches
Step Quantity:
5
Second End Spline Quantity:
36
Largest Step Diameter:
Between 0.497 inches and 0.498 inches
Surface Finish:
40.0 microinches
Special Features:
Splined shoulder 0.250 in. W, 1.688 in. From threaded end
Material:
Stainless steel

NSN 3040-00-024-5960

Shouldered Shaft - Page 2 of 2



Material Specification:

Ams-5610 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200