

View Online at <https://aerobasegroup.com/nsn/3040-00-050-0218>

Chamfer Angle In Deg:

10.0

Outside Diameter:

Between 0.365 inches and 0.370 inches

Thickness:

0.200 inches

Bore Diameter:

Between 0.2410 inches and 0.2430 inches

Largest Diameter Length:

0.070 inches

Securing Hole Quantity:

2

Angle Between Centerlines Of Securing Holes In Deg:

180.0

Securing Hole Type And Location:

Unthreaded all holes

Hole Diameter And Location:

0.0540 inches all holes and 0.0580 inches all holes

Material:

Steel, qq-s-763

Material:

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Round w/double chamfer

Surface Treatment:

Passivated, mil-s-5002

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A231a0