NSN 3040-00-055-4933

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-055-4933 First End Style: Splined (involute) **End Similarity:** Not identical Second End Style: Externally threaded and flat keyway **Overall Length:** 8.218 inches First End Diameter: Between 0.8090 inches and 0.8110 inches First End Spline Length: 0.938 inches First End Spline Minor Diameter: Between 0.8045 inches and 0.8125 inches First End Spline Major Diameter: Between 0.9033 inches and 0.9063 inches First End Pressure Angle: 30.0000 degrees First End Pitch Diameter: 0.8750 inches **Second End Keyway Width:** Between 0.2490 inches and 0.2495 inches Second End External Keyway Length: 0.750 inches **Second End Keyway Depth:** 0.104 inches **Second End Diameter:** Between 0.9835 inches and 0.9840 inches Second End External Thread Length: 0.531 inches Step Quantity: First End Spline Quantity: 28

Largest Step Diameter: 1.002 inches

Surface Finish:

16.0 microinches

Material:

Stainless steel

Material Specification:

Qq-s-763 federal specification single material response

NSN 3040-00-055-4933

Shouldered Shaft - Page 2 of 2



Fsc A	\pp	lication	Data:

Fan drive, engine, non-aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200